

SEPARATING PEOPLE FROM HAZARDS

KeeGuard® Safety Railing











- NON-PENETRATING SYSTEM: NO ROOF LEAKS
- COUNTERBALANCE ENGINEERING FOR MAXIMUM STRENGTH
- NO WELDING, BENDING, OR THREADING OF PIPE: EASY ASSEMBLY
- MEETS OSHA SAFETY STANDARDS FOR GUARDRAIL SYSTEMS

KeeGuard®

Engineered for Safety



Versatility

All Types. All Shapes. Even the Corners.

KeeGuard component railings use the original Kee Klamp modular system for multiple configurations and versatility on uniquely shaped installations. Only KeeGuard offers optimal stability for all standard rooftop systems including Membrane, Metal Profile, and Standing Seam up to 45°. KeeGuard is engineered to eliminate risk on any flat or low-slope roof including:

- · Composite Rooftop Systems
- · Roofs with Changes in Level
- · Complex Roof Shapes
- · Safe access to equipment located at roof edge
- · Green Roofs

LongevityPermanent Peace of Mind.

The KeeGuard guardrail system provides permanent, free-standing and durable edge protection without penetration of the roofing membrane or the building structure. The hot-dipped galvanized finish is corrosion resistant and low maintenance for safe and dependable rooftop edge protection.

AestheticsPowder Coated Colors.

KeeGuard's galvanized steel finish is corrosion-resistant and is available in a full range of powder coat RAL colors. Our 11°Angled Railing tilts back out of sight so the roof line offers a clean view from the ground.





KeeGuard® Features

- · Modular component system for multiple configurations
- · Adaptable to varying angles and radius edges
- · Accommodates ladders, equipment and rooftop obstructions
- Simple counterbalance construction made from 100% recycled PVC
- Durable galvanized finish is corrosion resistant

KeeGuard® Benefits

- · Non-penetrating solution roof membrane will not leak
- · Passive barrier that protects all personnel; no training required
- Integrates easily with your current fall protection products
- Lower installation cost than fabricated pipe
- No rooftop parapet required

Installing KeeGuard®

- KeeGuard Roof Edge Fall Protection System includes pipe railings, uprights, bases, counterweights and fittings
- No specialized labor or work permits, no welding
- Tools required: torque wrench or hex key

Compliance



Hierarchy of Fall Protection



- 1. Eliminate the Hazards
 - 2. Collective Fall Protection [OSHA: Passive]
- 3. Work Restraint [OSHA: Active]
- 🜟 4. Personal Fall Arrest System

OSHA Compliance

- OSHA Code 1910.28(b)(13) Unprotected Edges: Work on Low Slope Roofs
- · KeeGuard meets OSHA compliance for guardrail systems: Capable of withstanding, without failure, a force of at least 200 pounds (890 N) applied in a downward or outward direction within 2 inches (5 cm) of the top edge, at any point along the top rail
- OSHA regulations cite that on any building where work is performed within 15' of an open roof edge, each worker must be protected from the hazard of falling
- KeeGuard provides a safety barrier that requires no formal training or experience [it is passive] and "collectively" protects people when working at height

Protect your workforce, secure your roof with KeeGuard

STANDING SEAM | METAL PROFILE | MEMBRANE | COMPOSITE | GREEN ROOF



KeeGuard® TopFix

Metal Roof Perimeter Protection A smart solution for standing seam and metal profile roof systems.



KeeGuard® FoldShield

Folding Safety Rail System Maintain building aesthetics with cantilevered and foldable guardrail.



KeeGuard® Contractor

Upright, Weighted Guardrail Modular safety rail provides a secure barrier around tight areas. Free-standing and portable for temporary installations.

The Hierarchy of Fall Protection:



- fall is possible but the fall is
 "arrested" or interrupted

 The fall occurs within an acceptable
 force and calculated fall distance
 - Additional training and a high level of user competency is required
- Ability to work freely within the safe zone of the roof surface
- Work Restraint is the preferred system to mitigate the possibility of a fall



USA

Kee Safety, Inc. 100 Stradtman Street Buffalo, NY 14206

Tel: (716) 896 4949 Fax: (716) 896 5696 Toll Free: (800) 851 5181

www.keesafety.com Email: info@keesafety.com

Canada

Kee Safety, Ltd.

40 North Rivermede Road, Units 6 - 7

Concord, Ontario L4K 2H3

Tel: (905) 669 1494 Fax: (905) 669 4347

300) 851 5181 Toll Free: (877) 505 5003 řety.com

Kee Klamp, Kee Lite, Kee Stainless, KeeGuard, Kee Dome, Kee Hatch, Kee Mark, Kee Access, Kwik Kit, Kee Anchor, Weightanka, Wireanka, KeeLine, Kee Walk and Kee Projects are all registered trademarks of Kee Safety Ltd, Beam Clamp, and Box Bolt are all registered trademarks of Access Technologies Ltd, a subsidiary of Kee Safety International Ltd. While every effort has been made to ensure the accuracy of the information contained in this brochure, Kee Safety, Inc cannot be held responsibility for any errors or omissions. Kee Safety, Inc reserves the right to alter or withdraw products without prior notice.

Kee Safety, Inc does not accept responsibility for any loss or damage arising from improper use of its products.

Copyright 2018 Kee Safety, Inc. All Rights Reserved.